

Available Specification

Nominal Size		Outside Diameter		Class	Thickness	Mass of Black Pipe	
(DN)		Max	Min			Plain End	Screw and Socketed
in	mm	mm	mm			Kg/m	Kg/m
1/2	15	21.4	21.0	Light	2.00	0.947	0.956
		21.7	21.1	Medium	2.60	1.21	1.22
				Heavy	3.20	1.44	1.45
3/4	20	26.9	26.4	Light	2.30	1.38	1.39
		27.2	26.6	Medium	2.60	1.56	1.57
				Heavy	3.20	1.87	1.88
1	25	33.8	33.2	Light	2.30	1.98	2.00
		34.2	33.4	Medium	3.20	2.41	2.43
				Heavy	4.00	2.94	2.96
1 1/4	32	42.5	41.9	Light	2.60	2.54	2.57
		42.9	42.1	Medium	3.20	3.10	3.13
				Heavy	4.00	3.80	3.83
1 1/2	40	48.4	47.8	Light	2.90	3.23	3.27
		48.8	48.0	Medium	3.20	3.57	3.61
				Heavy	4.00	4.38	4.42
2	50	60.2	59.6	Light	2.90	4.08	4.15
		60.8	59.8	Medium	3.60	5.03	5.10
				Heavy	4.50	6.19	5.26
2 1/2	65	76.0	75.2	Light	3.20	5.71	5.83
		76.6	75.4	Medium	3.60	6.43	6.55
				Heavy	4.50	7.93	8.05
3	80	88.7	87.9	Light	3.20	6.72	6.89
		89.5	88.1	Medium	4.00	8.37	8.54
				Heavy	5.00	10.30	10.50
4	100	113.9	113	Light	3.60	9.75	10.00
		114.9	113.3	Medium	4.50	12.20	12.50
				Heavy	5.40	14.50	14.80
5	125	140.6	138.7	Medium	5.00	16.60	17.10
		140.6	138.7	Heavy	5.40	17.90	18.40
6	150	166.1	164.1	Medium	5.00	19.70	20.30
		166.1	164.1	Heavy	5.40	21.30	21.90